



QUALIFICATION NOTICE

April 09, 2007

PRODUCT: 95 Gallon Poly-Overpack Salvage Drum (ENPAC Part No. 1237-YE)

TESTING REFERENCE: TR-1636, 637, and 1638

REGULATION: United Nations General Recommendation on Packing for Transportation of Dangerous Goods, 49 CFR 173.3

OBJECTIVE: To determine the compliance with the applicable regulations for UN 1H2 container for Packing Group 1 solid materials and 49 CFR 173.3 Salvage Drum applications.

ITEMS TESTED: Required lot of removable top, open head plastic container. Volumetric capacity of the container is 95 gallons. Material of construction of the container is Linear Low Density Polyethylene (LLDPE) resin, rotationally molded.

RESULTS:

TEST	REGULATION	DESCRIPTION	PERFORMANCE
Drop	UN 6.1.5.3 49 CFR 178.603	1.8 meters, 295kg -18° Celsius	Passed
Leakproofness	UN 6.1.5.4 49 CFR 178.604	30 kPa 5 minutes	Passed
Stacking	UN 6.1.5.6 49 CFR 178.606	3 meters, 590 kg load 24 hours	Passed

CONCLUSION: Part design complies. Enpac Certified.

Load measured with Enpac's Filing Scale model DR 4000, calibrated and maintained by Filing Scale. Calibrated 1-07. Temperature maintained by a Duracool freezer indicator. Calibrated 3-07. Levels measured with a 1 year old Empire magnetic angle locator. Air pressure measured with an Omega digital pressure gauge. Calibrated 3-07

PACKAGING MARKINGS:



1H2/X295/S/07/USA/M4339

APPROVED BY:

DOUG HORNER, PRINCIPAL

KEITH HILL, QUALITY ASSURANCE TECHNICIAN

355 Yokes Drive Eastlake, Ohio 44095-4033 (440)975-0070 Fax (440)975-0047 Customer Service (800)936-7229